

4

Coreless Brushless DC Motor Membrane Air Pump



TMD40A-F Series Coreless Brushless DC Membrane Pressure / Vacuum Pump

Model	Pressure Pump	Vacuum Pump	Rated Voltage	No-load Current	Max Pressure	Max Vacuum	Max Flow
	(Item Number)	(Item Number)	(Vdc)	(A)	(KPa)	(KPa)	(L/min)
TMD40A-F	TMD40A-F12-P22017 (outside controller) in parallel double outputs		12 / 24	1.8	220		17
		TMD40A-F12-V7517 (outside controller) in parallel double outputs	12 / 24	1.8		-75	17
		TMD40A-F12-V9512 (outside controller) in series single output	12 / 24	1.8		-95	12

"P" means pressure pump, "V" means vacuum pump, "12/24" means different voltages optional.

Pump Weight:540g; Pump Size:144mm*52mm*65mm; Inlet&Outlet:OD 6.5mm/ID 3.4mm, hose suggestion:ID 5.0mm

Super silent noise; Materials:pump head Nylon, membrane EPDM / PTFE, valve EPDM / FPM

Motor type and code: "F"means Coreless brushless DC motor with dual ball bearings + outside controller (long lifetime 15,000hours);pump with outside controller can realize functions of speed adjustment, brake, instant starting work; inner controller is no additional functions.



