

ZWMD016017

Application: Automechanism transmission, Medical applications, Ad rotaion transmission, ATM , and etc.

Output Power: 0.1W~2W

Metal output shaft

Standard Plastic Geared Motor

Model	Application Parameters							Overall Length	Rated Torque of Gear Box	Instant Torque of Gear Box	Gear Ratio	Gear Box Length
	Rated	At No Load		At Rated Load			Torque 转矩					
	Voltage	Speed	Current	Speed	Current							
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m		mm	gf.cm		gf.cm
ZWMD016017-4	9.0	1838	95	1625	165	16	1.6	34.2	1500	10000	4	11.5
ZWMD016017-6	9.0	1225	95	1083	165	24	2.4		1000	10000	6	
ZWMD016017-16	9.0	460	105	406	165	51	5.0	37.5	2500	10000	16	14.8
ZWMD016017-24	9.0	306	105	271	165	77	7.5		2500	10000	24	
ZWMD016017-36	9.0	204	105	181	165	115	11.3		2000	10000	36	
ZWMD016017-64	9.0	115	115	102	165	135	13.2	40.8	3500	10000	64	18.1
ZWMD016017-96	9.0	77	115	68	165	203	19.9		3500	10000	96	
ZWMD016017-144	9.0	51	115	45	165	304	29.8		3500	10000	144	
ZWMD016017-216	9.0	34	115	30	165	456	44.7		3000	10000	216	
ZWMD016017-256	9.0	29	115	25	170	405	39.7	44.1	5000	10000	256	21.4
ZWMD016017-384	9.0	19	115	17	170	608	60		5000	10000	384	
ZWMD016017-576	9.0	13	115	11	170	911	89		5000	10000	576	
ZWMD016017-864	9.0	9	115	8	170	1367	134		5000	10000	864	
ZWMD016017-1296	9.0	6	115	5	170	2050	201		3500	10000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements.

